



Integra[®] View Workstations

Control Center Performance. Intelligently Delivered.

The IndigoVision Integra[®] View Workstations are designed and configured for easy installation and enable the connection and management of multiple Integra[®] as a single site. The Integra[®] View Mini Workstation supports up to 24 Channels of video across multiple Integra[®]. Supporting up to four monitors, the IndigoVision Integra[®] View Mid Workstation is for sites with more than 24 Channels of video. Designed and pre-installed with Control Center Integra[®] View each workstation delivers guaranteed performance.

Key Features

COMPRESSION

H.264	MJPEG	MPEG-4	AAC	G.711
--------------	--------------	---------------	------------	--------------

OTHER

DNA	
------------	--

PHYSICAL

TOWER

Product Codes

Integra [®] View Workstations	Product Code
Integra [®] View Mini Workstation (G2) (up to 24 channels)	980610
Integra [®] View Mid Workstation (G2) (unlimited channels)	980613

Specifications

General Specifications	Mid Workstation	Mini Workstation
Live Viewing Performance*	98 4SIF streams at 30fps, 18 HD streams at 30fps, 10 4MP streams at 30fps, 5 4K streams at 30fps	34 4SIF streams at 30fps, 5 HD streams at 30fps, 2 4MP streams at 30fps, 1 4K streams at 30fps
Playback Viewing Performance*	25 4SIF streams at 30fps, 11 HD streams at 30fps, 8 4MP streams at 30fps, 3 4K streams at 30fps	25 4SIF streams at 30fps, 6 HD streams at 30fps, 3 4MP streams at 30fps, 1 4K streams at 30fps
Operating System	Windows 10 64bit (IoT Enterprise Embedded 2016, Multi-Language)	
Processor	Intel® Core™ i7 (3.2Ghz)	Intel Core™ i5 (2.8Ghz)
Memory	16GB DDR4 (2x8GB, 2666MHz)	8GB DDR4 (2666MHz)
O/S Hard Disk	256GB SSD (PCIe NVMe Class 40) plus 4TB 3.5in SATA	256GB SSD (PCIe NVMe Class 40)
Network Interface	100/1000 BaseT RJ-45	
Video Interface	Radeon Pro WX 2100 2GB supporting up to three HD or three 4K monitor output or five HD monitors if using DisplayPort MST	2x DisplayPort, Integrated Intel HD Graphics supporting dual monitor output
Audio Interface	HDMI, Mic In, Headphone, Line In/Out	
Form Factor	Mini Tower Form Factor Chassis	Compact Micro Form Factor Chassis
Dimensions/Weight	345mm (d) x 176.6mm (w) x 335mm (h) and 9.36Kg	178mm (d) x 36mm (w) x 182mm (h) and 1.18Kg
Electrical	460W (100 to 240 VAC, 50/60 Hz, auto switching). 90% efficient PSU (80PLUS Gold Certified Certified) Energy Star compliant	130W Adaptor (100 to 240 VAC, 50/60 Hz, auto switching). Minimum Efficiency > 87%, ENERGY STAR compliant
Regulatory	EN 60950-1, IEC 60950-1, EN 55022, CISPR 22, EN 61000-3-2, EN 55024, IEC 61000-3-2 (Class D), EN 61000-3-3, IEC 61000-3-3, CISPR 24	
Housing	Mild Steel Chassis and Polycarbonate Fascia	
Temperature	Operating: 10 °C to 35 °C Storage: -40° C to 65° C	
Humidity	20% to 80% relative humidity (non-condensing)	
Vibration	Operating: 5 Hz to 350 Hz at 0.0002 G ² /Hz Storage: 5 Hz to 500 Hz at 0.001 to 0.01 G ² /Hz	
Shock	Operating: 40 G +/- 5% with pulse duration of 2 msec +/- 10% (equivalent to 51 cm/sec) Storage: 105 G +/- 5% with pulse duration of 2 msec +/- 10% (equivalent to 127 cm/sec)	
Altitude	Operating: -15.2 m to 3048 m Storage: -15.2 m to 10,668 m	
Supplied Accessories	USB Mouse, Regional Power Cord, 2 x mDP to DisplayPort cables, 8x Slimline DVD+/-RW Drive	USB Mouse, Regional Power Cord
Software Requirements	Control Center v15.3 will come pre-installed	

*Viewing figures achieved using two HD Monitors for live viewing and H.264.

Accessories

Accessories	Product Code
Workstation Monitor 24in 1080p 60Hz	110390
Workstation Keyboard (USB) - US International	110385
Workstation Keyboard (USB) – UK English	110384
Workstation Keyboard (USB) – Spanish	110383
Workstation Keyboard (USB) – Italian	110382
Workstation Keyboard (USB) – German	110381
Workstation Keyboard (USB) – French	110380
Workstation Keyboard (USB) – Arabic	110386