



IndigoVision

WORKSTATIONS



# Mini Client Workstation

Control Center Performance. Intelligently Delivered.

The IndigoVision Mini Client Workstation is a small but powerful machine that is perfect when space is limited in your Control Room. Lightning fast boot times are made possible with a Solid State Hard Drive and 8GB of high speed memory. Designed and configured for easy installation of Control Center with performance guaranteed.

## Key Features

COMPRESSION

**H.264**

  
**H.264**

**JPEG 2000**

**MJPEG**

**MPEG-4**

  
**AAC**

  
**G.711**

OTHER

  
**DNA**



PHYSICAL

  
**MINI**

## Product Codes

Mini Client Workstation	Product Code
Mini Client Workstation	980627

# Specifications

General Specifications	
Live Viewing Performance	34 4SIF streams at 30fps, 5 HD streams at 30fps, 2 4MP streams at 30fps, 1 4K streams at 30fps
Playback Viewing Performance	25 4SIF streams at 30fps, 6 HD streams at 30fps, 3 4MP streams at 30fps, 1 4K streams at 30fps For complete live viewing performance specification please refer to the Control Center v15.0 Performance Reference Guide, available on the IndigoVision Partner Website
Operating System	Windows 10 64bit (IoT Enterprise 2016, Multi-Language)
Processor	Intel® Core™ i5 (2.8Ghz)
Memory	8GB DDR4 (2666MHz)
O/S Hard Disk	256GB SSD (PCIe NVMe Class 40)
Network Interface	100/1000 BaseT RJ-45
Video Interface	2x DisplayPort, Integrated Intel UHD Graphics supporting dual monitor output
Audio Interface	Mic In, Headphone, Line Out
Form Factor	Compact Micro Form Factor Chassis
Dimensions/Weight	178mm (d) x 36mm (w) x 182mm (h) and 1.18Kg / 7.0in (d) x 1.4in (w) x 7.2in (h) and 2.6lb
Electrical	130W Adaptor (100 to 240 VAC, 50/60 Hz, auto switching). Minimum Efficiency > 87%, ENERGY STAR compliant
Regulatory	EN 60950-1, IEC 60950-1, EN 55032:2012/CISPR 32:2012, EN 55032:2015/CISPR 32:2015, EN 55024:2010 +A1:2015/CISPR 24:2010 +A1:2015, EN 61000-3-2:2014/IEC 61000-3-2:2014 (Class D), EN 61000-3-3:2013/IEC 61000-3-3:2013, DRAFT EN 301 489-1 V2.2.0, DRAFT EN 301 489-17 V3.2.0
Housing	Mild Steel Chassis and Polycarbonate Fascia
Temperature	Operating: 10°C to 35°C (50°F to 95°F) Storage: -40°C to 65°C (-40°F to 149°F)
Humidity	20% to 80% relative humidity (non-condensing)
Vibration	Operating: 5 Hz to 350 Hz at 0.0002 G <sup>2</sup> /Hz Storage: 5 Hz to 500 Hz at 0.001 to 0.01 G <sup>2</sup> /Hz
Shock	Operating: 40 G +/- 5% with pulse duration of 2 msec +/- 10% (equivalent to 51 cm/sec) Storage: 105 G +/- 5% with pulse duration of 2 msec +/- 10% (equivalent to 127 cm/sec)
Altitude	Operating: -50ft to 10,000 ft Storage: -50ft to 35,000ft
Supplied Accessories	USB Mouse, Regional Power Cord
Software Requirements	Control Center v15.3 (pre-installed)

## Accessories

Accessories	Product Code
Workstation Monitor 24in 1080p 60Hz	110390
Workstation Keyboard (USB) - US International	110385
Workstation Keyboard (USB) – UK English	110384
Workstation Keyboard (USB) – Spanish	110383
Workstation Keyboard (USB) – Italian	110382
Workstation Keyboard (USB) – German	110381
Workstation Keyboard (USB) – French	110380
Workstation Keyboard (USB) – Arabic	110386